

SPECIFICATIONS

20" alloys in lieu of 22" alloys
LED Headlights with signature DRL in lieu of Pixel LED headlights with signature DRL
12 way seats in lieu of 22 way seats
Non heated steering wheel
Unpainted brake callipers
Grained leather seats in lieu of Perforated semi aniline Leather
Two Zone climate control in lieu of Four Zone
Sunvisor with illuminated vanity mirror

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

CO₂ Emissions (from) (g/km)

Fuel consumption (up to) (mpg)

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. † Includes full fluids and 90% fuel. ††Roof carrying is only available with fixed and sliding panoramic roofs

Maximum speed mph (km/h)	150 (242)
Acceleration (secs) 0-60 mph (0-100 km/h) with Dynamic Launch	4.7 (4.9)

Capacity (cc)	2,996
Maximum power (PS/rpm)	550 / 5,500-6,500
Maximum torque (Nm/rpm)	800 / 2,000 -5,000
Transmission	Automatic
Fuel tank capacity - useable litres	71.5

Unladen weight (EU)**	2,810
Unladen weight (DIN) †	2,735
Gross Vehicle Weight (GVW)	3,450

Unbraked trailer	750
Maximum towing	3,000
Maximum coupling point (nose weight)	120
Maximum vehicle and trailer combination	6,450

Maximum roof load (including cross bars)	100
--	-----

Maximum height (mm)	1,820
Overall length (mm)	4,946
Width with mirrors folded (mm)	2,047
Width with mirrors out (mm)	2,209
Front wheel track (mm)	1,702
Rear wheel track (mm)	1,704
Wheelbase (mm)	2,997

Maximum front row headroom (mm)	998
Maximum second row headroom (mm)	982

Maximum first row legroom (mm)	1,024
Maximum second row legroom (mm)	961

Height (mm)	793
Width (mm)	1,400
Width between arches (mm)	1,103
Length behind first row (mm)	1,827
Maximum loadspace volume behind first row - Dry (litres)	1,491
Maximum loadspace volume behind first row - Wet (litres)	1,860
Length behind second row (mm)	970
Maximum loadspace volume behind second row - Dry (litres)	647
Maximum loadspace volume behind second row - Wet (litres)	835

Ride height (mm)	216 / 209
Approach angle	- 26.1° / 22.5°
Departure angle	- 25°
Ramp angle	- 21.5° / 26.7°

Ride height (mm)	280 / 273
Approach angle	- 33.0° / 29.7°
Departure angle	- 29.8°
Ramp angle	- 26.9° / 24.4°

Maximum wading depth (mm)	900
---------------------------	-----

Kerb-to-kerb Two wheel steering (m)	12.53
Kerb-to-kerb Four wheel steering (m)	10.95
Wall-to-wall Two wheel steering (m)	12.53
Wall-to-wall Four wheel steering (m)	10.59
Turns lock-to-lock (no. of turns)	2.8